

Porvene

model 600



Standard Features:

- 1. Insulated Slat Curtain**
 - › Environmentally Safe Polyisocyanurate insulating material housed between a 22 gauge front slat and a 24 gauge back slat.
- 2. Guides**
 - › Structural steel wall angle with vinyl jamb weatherseal.
- 3. Bottom Bar**
 - › Two 2" X 2" X 1/8" structural steel angles form a rugged bottom bar assembly. A vinyl bulb astragal helps to conform to floor irregularities and helps guard against weather, dirt, insects and rodents.
- 4. Pipe Barrel**
 - › Continuous minimum 6" diameter pipe to support door curtain with no more than .03" of deflection per foot of width.
- 5. Counterbalance**
 - › Standard 20,000 cycle helical torsion spring.
- 6. Door Stops**
 - › Removable stops located on inside and outside of the guides for added safety.
- 7. Hood**
 - › 24 Gauge galvanized steel with a baked enamel prime finish hood including an 8" P.V.C. baffle to help seal out the elements.
- 8. Chain Hoist**
 - › Heavy duty #50 roller chain and sprockets combined with a smooth hand-chain provides for safe and efficient operation. Removal of chain hoist makes door Electric Operation ready without further modification or cost.
- 9. Slide Bolt Locks**
 - › Can accommodate padlocks (optional).

Model 600: Therm-Master Steel Backed Insulated Door

Porvene's 600 Series Therm-Master Steel Backed Insulated Doors offers insulating values of R-Factor =5.4 and U-Factor=0.185. The insulation material is made from environmentally safe Polyisocyanurate with aluminum facers adhered to the effective thermal barrier. The Model 600 was tested for sound transmission in accordance with ASTM E 413-87 and was given a rating of STC-23. Powder Coating in a wide variety of colors is also available. This product line comes standard with Chain Operation and can be upgraded to Electric Operation.

Other Options:

- › Powder coating
- › Higher than 20 P.S.F. windloading available
- › High cycle option available
- › Cylinder lock
- › Cast iron end locks/ windlocks

Porvene



options electric operator

Options:



> View Lite



> **Wicket Door** Provides roll-up and pass door convenience while maintaining access to full opening width



> **Pass Door**



> **Safety Brake Bearing**

Distributor:

Porvene is an authorized Master Distributor for LiftMaster® products. For a complete list of all options and modifications, please contact your local Porvene Distributor.

CHAMBERLAIN®

LiftMaster®

PROFESSIONAL

Options



> **Model H**
Industrial Duty Hoist Operator

> **Model GH**
Heavy Industrial Duty Gear-Reduced Operator

- > Non-contact infrared reversing sensors
- > Audible Warning Light
- > Remote Controls
- > Interlock Switch
- > Miller Electric Sensing Edge
- > Alarm Bell
- > Tamper Proof Key Station
- > Card Readers
- > Digital Key Pad
- > Telephone Entry System

Model 600 Head Plates/Guides & Endlocks

		HEIGHT (FT)																																																							
		5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30																														
WIDTH (FT)	5																																																								
	6																																																								
	7																													TYPE 2 GUIDES 14" HEADPLATE	TYPE 2 GUIDES 16" HEADPLATE						TYPE 4 GUIDES 22" HEADPLATE																				
	8																																																								
	9																																																								
	10																																																								
	11																																																								
	12																																																								
	13																																																								
	14																																																								
	15																																																								
	16																																																								
	17																																																								
	18																																																								
	19																																																								
	20																																																								
	21																																																								
	22																																																								
	23																																																								

Stamped End locks
Cast End locks
Malleable Wind locks

14" HEADPLATES	16" HEADPLATES	22" HEADPLATES
x=19"	x=21"	x=28"
v=15"	v=17"	v=23"