




HANDICAPPED THRESHOLD



SECTION A - A


GENERAL NOTES		
RIGHT HAND WICKET SHOWN, LEFT OPPOSITE OPERATION	A1"	A2"
ELECTRIC OPERATION	9	6
CAST REDUCTION	9	6
ALL REDUCTION ON DOORS 14" WIDE OR WIDER	10	7




U-GUIDE FOR STEEL/WOOD

Z-GUIDE FOR CONCRETE/MASONRY


2 PC. GUIDES	A"	B"	C"	D"	E"	F"
	2 1/2	3 13/16	4 1/2	1 1/4	2 5/8	2 1/16



GAUGE



GAUGE



PANIC BAR HARDWARE  
HOLLOW METAL DOOR

02-18-03

300-Wicket-L

MRK.	QTY.	OPENING SIZE		OPERATION	RH LH	CLEARANCES		OPTION	PROJECT:									
		WIDTH "W"	HEIGHT "H"			"X"	"V"		ARCHITECT:	CONTRACTOR:	DISTRIBUTOR:	DATE:	SHEET: OF:	BY:	REF. #:			



NOTE: Porvene Doors is not responsible for improper installation procedures, structural backing, and field inspections of the project itself.

APPROVAL SIGNATURE:

DATE:

300 SERIES-COMMERCIAL SLAT DOOR/L.H. WICKET