



FOR BETWEEN JAMB		FOR BETWEEN JAMB				
GUIDE TYPE	A"	B"	C"	D"	E"	F"
Z	3	4 1/4	5 1/2	5/8		3
E		1 15/16	3 1/2	5/8	3 3/16	3
SQ3			6	5/8	3	3
SQ4			7	7/8	4	3

MINIMUM SIDE ROOM CLEARANCES REQUIREMENTS:

	PUSH	PULL
DRIVE		6"
TENSION		6"

GENERAL NOTES

- STANDARD: CURTAIN: TO BE CLEAR ANODIZED HOLLOW TUBES OVER COLD ROLLED STEEL RODS. MILL FINISH LINKS.
- BOTTOM BAR: CLEAR ANODIZED ALUMINUM.
- GUIDES: CLEAR ANODIZED ALUMINUM WITH POLYETHYLENE INSERT.
- NON ALUMINUM SURFACES: TO BE SHOP COATED WITH RUST INHIBITING PRIMER.
- OPERATION: MANUAL PUSH/PULL UP TO 10' X 10' MAX.

02-15-02

500-MANUAL

MRK.	QTY.	OPENING SIZE		OPERATION	RH LH	CLEARANCES		OPTION	PROJECT:	ARCHITECT:	CONTRACTOR:	DISTRIBUTOR:	DATE:	SHEET:	OF:	BY:	REF. #.	
		WIDTH "W"	HEIGHT "H"			"X"	"Y"											
MODEL 500 - STANDARD STRAIGHT STYLE GRILLE																		



NOTE: Porvene Doors is not responsible for improper installation procedures, structural backing, and field inspections of the project itself.

APPROVAL SIGNATURE:

DATE: